

# DISHWASHER AIR GAP

**/// 249 SERIES**

**SPECIFICATION**

Tomahawk dishwasher air gap shall be installed where a dishwasher air gap is required. Air gap device shall be designed with 1/2" inlet hose barb and 3/4" outlet hose barb. Product shall conform to ASSE 1021. Waste discharge from dishwasher shall not be less than 5 gpm with inlet pressure not over 5 psi at inlet connection.

**MATERIALS**

**Body and nut:** polypropylene  
**Cap:** chrome-plated brass or chrome-plated polypropylene

**INSTALLATION**

Product must be installed according to national or local plumbing codes. All hoses must be connected with approved hose clamps (not provided). Connect inlet to dishwasher. Connect discharge outlet to garbage disposal.

**CONNECTION**

**Inlet:** 1/2" hose barb  
**Outlet:** 3/4" hose barb


**DIMENSIONS**

- A: cap width 1.712"
- B: cap height 2.438"
- C: overall height 8.75" – 9.25"
- D: inlet 1/2" hose barb
- E: outlet 3/4" hose barb

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



249-20135



**Create Item Number**

**249-A**

e.g. **249:** heavy-duty air gap with chrome-plated brass cap

**STYLE A**

- \_ = (leave blank) heavy-duty air gap with chrome-plated brass cap
- 20135 = economy air gap with chrome-plated poly cap

