WATER HEATER TEE ADAPTERS

>> 687 SERIES

SPECIFICATION

Sioux Chief 687 series water heater tee adapters shall be used where necessary to provide convenient connection access for expansion tanks, valves and other accessories in hot and cold water distribution systems. FIP swivel connections shall include EPDM sealing gaskets. All connection options shall conform to appropriate standards, including ASTM thread specifications.

MATERIALS

Brass¹ tee body, EPDM gaskets

INSTALLATION NOTES

Do Not use pipe dope or thread tape on FIP swivel connections. Always follow local plumbing/building codes.


DIMENSIONS

		687-T3MMS	687-T3MSM	687-T3MSS
A:	Trunk 1	3/4" MIP ²	3/4" MIP ²	3/4" MIP ²
B:	Trunk 2	3/4" MIP ²	3/4" FIP swivel	3/4" FIP swivel
C:	Branch	3/4" FIP swivel	3/4" MIP ²	3/4" FIP swivel
D:	Overall height	1.75"	1.88"	1.75"
E:	Overall width	2.52"	2.52"	2.52"

¹ Material is C46500. Brass is dezincification and SCC resistant, and is compliant with NSF-61 Annex G and California No Lead Plumbing Law







Item Number

687-A

e.g. 687-T3MMS: Brass tee adapter - 3/4" MIP x 3/4" MIP x 3/4" FIP Swivel

CONNECTION TYPE A

T3MMS = 3/4" MIP x 3/4" MIP x 3/4" FIP Swivel (trunk x trunk x branch)

T3MSM = 3/4" MIP x 3/4" FIP Swivel x 3/4" MIP (trunk x trunk x branch)

T3MSS = 3/4" MIP x 3/4" FIP Swivel x 3/4" FIP Swivel (trunk x trunk x branch)

Other Water Heather Accessories - Available Separately:

648-3SM: 600 WOG Brass Ball Valve: 3/4" FIP Swivel x 3/4" MIP

648-3SW: 600 WOG Brass Ball Valve:

3/4" FIP Swivel x 3/4" F1960 PEX

648-3SX: 600 WOG Brass Ball Valve: 3/4" FIP Swivel x 3/4" F1807 PEX

² MIP connection IDs are sized to accept check valve installation