

P.O. Box 397, 24110 South Peculiar Drive
Peculiar, Missouri 64078 U.S.A.
tel: 1-800-821-3944 • 816-779-6104
fax: 1-800-758-5950 • 816-758-5950
www.siouxchief.com



TECHNICAL BULLETIN

DATE: March 31, 2008

RE: **Suspensulator – Acceptable Dual Purpose Applications**

Sioux Chief Manufacturing's Suspensulator product is to be used to isolate or suspend 3/8" – 1" CTS tubing. This dual-purpose product can be installed as an insulator in either wood or metal studs, or it can be installed by fastening directly to a wood or stud to help stabilize and hang long pipe runs.

When used as an isolator, the installer should bore a 1-3/8" hole in the wood stud. When used in metal studs, the installer should punch or drill a 1-11/32 hole in the metal stud. When isolating pipe to prevent surface contact, the two mounting holes do not require any type of fastener or hardware. The fins are sized and designed to fit either hole size, and expand and lock into the stud member once the tube is installed.

When used to suspend tubing from either a joist or stud, we recommend that installers use #6 or #8 screws or nails to fit the .150 hole dimension in the mounting ears.

If you have any questions regarding this product, please don't hesitate to call me at (800) 821-3944, Ext. 290. Thank you for considering and/or using Sioux Chief products.

Sincerely,

Carol Flanagan
Product Group Director – Support

